

MATERIAL SAFETY DATA SHEET

Section I - Product and Company Information

Product Name:	Extreme Texture Coat
CAS Number:	Mixture
Hazard Rating:	Health: 1 Fire: 1 Reactivity: 0 PPI: E
EPA Registration:	NA
Company Identification:	Acrylic Technologies, Inc. 8914 NE Alderwood Road Portland, Oregon 97220
Contact: Telephone/Fax: Emergency Phone (24 Hour):	CUSTOMER SERVICE (503) 282-2591 / (503) 552-1441 INFOTRAC (800) 535-5053
Product Class:	Waterbase Paint
Trade Name:	Extreme Texture Coat

Section II - Ingredient And Hazard Information

NFPA (USA)	WHMIS (Canada)	Transport Symbol
NA	NA	NA

Hazardous Ingredients: CAS Number % TSCA Health Fire React PP (No hazardous ingredients known at this time.)

Section III - Hazards Identification		
Primary Routes of Entry:	Ingestion and/or inhalation.	
Carcinogenicity:	This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.	
Acute (Short Term) For Product:	EYES: Causes irritation. SKIN: May cause skin irritation upon prolonged or repeated contact. BREATHING: Causes slight irritation to nose and throat. SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.	
Chronic (Long Term) For Produc	ct or Components: Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.	

MSDS Name: Extreme Texture Coat MSDS Number: CTTC-01 MSDS Date: June 1, 2011

Permissible Exposure Level for Product:

No Threshold Limit Value (TLV) has been established for the product. Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m³ as Inhalable Particulates Not Otherwise Classified for sprays, mists or dust particulates generated during application or handling exposures.

Section IV - First Aid Measures		
If In Eyes:	Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.	
If On Skin:	Flush skin with water.	
If Swallowed:	Induce vomiting. Call a physician immediately. Give large amounts of water or milk. Never give anything by mouth to an unconscious or convulsing person.	
If Breathed:	Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to- mouth. If breathing is difficult, give oxygen. Call a physician.	

Section V - Fire-fighting Measures	
Flammability Class:	IIIB
Flash Range:	>200F
Explosive Range:	Not Applicable.
Extinguishing Media:	Product is non-combustible.
Special Firefighting Procedures:	Use self-contained breathing apparatus with full face piece.
Unusual Fire & Explosion Hazards:	None.

Section VI - Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Small Spills:	Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.
Large Spills:	Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.
Note:	Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

Section VII - Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Protect From Freezing:Store above 40°F. Frozen product may be irreversibly damaged.
Keep container closed when not using. Agitate before using.

Section VIII - Exposure Controls/Personal Protection

Occupational Exposure Limits:	ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL		
Respiratory Protection:	Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.		
Ventilation:	Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.		
Protective Gloves:	None normally required. Use is advisable.		
Eye Protection:	Wear approved splash proof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.		
Other Protective Equipment:	Avoid contact with clothing, dried product may be irremovable.		

Section IX - Physical And Chemical Properties		
Form:	Liquid	
Appearance/Colour:	White	
Odour:	Mild	
Solubility (in water):	Dispersible	
pH Value:	9.5 - 10.0	
Boiling Range:	(Water) 212°F (100°C)	
Vapour Pressure (mmHg):	(Water) 17.@ 68°F (20°C)	
Melting Point:	Not Available	
Evaporation Rate:	Unavailable	
Vapour Density:	Non Volatile	
Partition Coefficient:	Not Available	
% Volatile Volume:	Including Water 53.54% / 53.65%	
Specific Gravity:	1.42642 / 1.42469	
VOC:	See Section XVI	
Molecular Weight:	Mixture	

Section X - Stability and Reactivity	
Stability:	This product is stable
Hazardous Polymerization:	Hazardous polymerization will not occur
Incompatability:	None
Conditions To Avoid:	Acids, strong oxidizing agents.
Hazardous Decomposition Products:	

Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

Section XI - Toxicological Information

Lethal Dose Information (ppm)

Additional Toxicological Data For Product And/or Ingredients:

None known for product.

Section XII - Ecological Information

ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS:

Aquatic toxicity not available.

Section XIII - Disposal Considerations

EPA Hazardous Waste Number: None

WASTE DISPOSAL METHOD: Product must be disposed of properly under Federal/State regulations for industrial waste. Disposal to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

Section XIV - Transport Information	
UN Number:	None
UN Pack Group:	NA
UN Class:	NA
ICAO/IATA Class:	None
DOT Hazard Class:	Not Hazardous

MSDS Name:Extreme Texture CoatMSDS Number:CTTC-01MSDS Date:June 1, 2011

CANADIAN TDG/WHMIS INFORMATION:

Pin Number:	None
Tdg:	NA
Tdg Act Class:	NA
Whmis:	NA
Other Names:	None

Section XV - Regulatory Information

Chemical Name:	CAS Number	%
Chlorothalonil:	1897-45-6	< 0.1
EEC Classification:	Irritant	

This product is not a listed hazardous substance.

Section XVI - Other Information

Additional Precautions And Notes:

Do not dilute or mix with other materials unless advised by supplier.

Voc Information:

VOC Content: Less than 50 grams per liter.