

DRYROOF® SA

WATERPROOFING UNDERLAYMENT

Lightweight Underlayment for Performance in Warm & Wet Climates

DryRoof® SA is a lightweight, self-adhering underlayment that provides a watertight seal around fasteners and roof penetrations to prevent leaks and water damage.

Designed for use in conjunction with asphalt shingles, DryRoof SA meets the requirements for use in a CertainTeed Integrity Roof System, providing contractors with a cost-effective underlayment option for offering manufacturer-backed extended roof system warranties.

- Weight per roll: 45 lbs
- Roll Area: 195 sq ft
- Roll Length: 65 ft
- Roll Width: 36 in
- Rolls per pallet: 33

DryRoof SA can be used to cover the entire roof deck, serving as a valley liner, roof penetration shield, and wind driven rain guard.

DryRoof SA meets the following applicable code requirement standards:

- ICC ESR-1492
- ASTM D1970; D2523; D903; D1204; D4073; E96
- Florida Product Approval #30046
- Miami-Dade Product Control Acceptance
- CSA A123.22
- UL 790: Classified for use as underlayment beneath Class A, B, or C fire rated shingle systems

DRYROOF® SA WATERPROOFING UNDERLAYMENT

Built to Endure

- UV exposure resistant for 6 months
- Warranted against manufacturing defects
- Warranted to remain watertight for the same warranty duration period carried by the shingles applied above it, up to a maximum of 50 years

Quick to Install

- Split-release backing and self-adhering application allow for fast and secure installation

Easier to Handle, Safer to Walk

- Sticks well to most surfaces
- Excellent elasticity delivers great stretch
- Sand surface is slip-resistant to reduce risk of falls



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com