

CertainTeed

EXTREME Texture Coat

Acrylic Texture with M2Tech®

Product Data and Submittal

Product Description

- Highly durable and scrubbable
- Not abrasive to skin
- Mold resistant
- Production spray application
- Orange peel and knockdown textures
- Scratch and abuse resistant surface without being abrasive itself
- Performs better in ASTM D2486 scrubbability tests than high gloss acrylic
- Highest possible score for mold resistance under ASTM 3273

Extreme Texture Coat provides a durable scratch and abuse resistant coating for interior walls and ceilings. You can scrub it clean without damaging its surface, yet it's non-abrasive to the skin. This acrylic based, ready mix, non-aggregate coating performs better in ASTM D2486 testing than high gloss acrylic. Extreme Texture Coat creates a durable and mold resistant surface for orange peel and knockdown textures.

Product Data

Colour: White

Finish: Flat

Packaging: 5 US Gal. (18.9 L) Pail

Coverage: Approximately 150 square feet per gallon for medium orange peel or knockdown texture applied at 10 wet mils.

Shelf Life: One year when properly stored and sealed.

Storage: Store materials in a dry area. Protect materials from direct sunlight. Store materials at a temperature between 40°F – 90°F (4°C – 33°C). Do not allow product to freeze. Product will not recover.

Recommended Mil Rate: Apply product at 10 wet mils.

Technical References: For additional information on the application and finishing of Gypsum Board please consult:

- ASTM C 840: Standard Specification for Application and Finishing of Gypsum Board.
- GA-214: Gypsum Association publication "Levels of Gypsum Board Finish."
- GA-216: Gypsum Association publication "Recommended Specifications for the Application and Finishing of Gypsum Board."

Working with the Product

Preparation for Substrate of New Gypsum

1. Surface must be clean, dry, sound and properly cured.
2. Surface must be completely dry before application.
3. As with most coatings, product should acclimate for 12 hours to the same temperature as the walls.

Preparation

1. Walls need to be dust free, dry and ready for paint.
2. You must mask the same as you would for paint.
3. Remove heavy dust residue from bottom of wall so dust doesn't blow upward on the wall. Wipe or sponge down paper fuzz prior to application.
4. Can be thinned by adding no more than one pint of water per five gallons. Do not over thin as over thinning could affect product performance.

Continued on back

Job Name

Contractor

Date

Products Specified:

Submittal Approvals
(Stamps or Signatures)

CertainTeed
SAINT-GOBAIN

Spray-on Application

Apply Extreme Texture Coat with portable texture sprayer, spray rig or hand-held hopper. Spray as you would any orange peel or knockdown texture. Prime with CertainTeed Level V M2Tech and finish with topcoat of paint. Product is bucket ready. Clean tools, equipment and skin with soapy water and rinse.

MSDS

MSDS Material Safety Data Sheets are available on our web site, www.CertainTeed.com.

Warning

Dust generated from sanding product may cause eye, skin, nose, throat or respiratory irritation. Use wet-sanding to avoid creating dust. Avoid inhalation of dust and eye contact. Product contains silica. Inhalation of respirable silica dust can cause silicosis, a potentially disabling lung disease, known to cause lung cancer.

When sanding, drilling or abrading product during installation or handling:

- (1) Ensure adequate ventilation.
- (2) Wear a dust mask or, if dust may exceed PEL, use NIOSH/MSHA approved respirator.
- (3) Warn others in area.
- (4) Wear eye protection. If eye contact occurs, flush with lukewarm, gently flowing water for 5 minutes or until particle/dust is removed.

For further information, refer to Material Safety Data Sheet or consult manufacturer by calling 1-800-327-7455.

KEEP OUT OF REACH OF CHILDREN.

Warranty

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum, Inc. (CertainTeed) will not be responsible for the failure of this Product when the Product is not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. Provincial or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS
GYPSUM • CEILINGS • INSULATION • PIPE

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

©09-2011 CertainTeed Gypsum, Inc. Rev 11-2012
Printed in Canada on recycled paper. CTG-4063