

# **GYPSUM SMOOTH**



Exceptional performance in high-moisture environments and exterior spaces.

#### **FEATURES AND BENEFITS**

- Paperless, glass mat faced gypsum board that is inherently mold-resistant
- Sag resistant with exceptional indoor/outdoor performance in applications up to 95% relative humidity
- Vinyl facing cleanable with most sanitizing chemicals
- Wash tested to 2,000+ cycles with no sign of wear
- Suited as clean room component to ISO Class 5
- Satisfies USDA/FSIS guidelines for sanitary applications
- Environmental Product Declaration (EPD) available for this product

#### **ATTRIBUTES**







LR 0.78



WASHABLE W/ SANITIZING CHEMICALS



COMPLIANT CERTIFIED

## LEED® v4

|                  |   | 93%      |          |  |  |  |  |  |
|------------------|---|----------|----------|--|--|--|--|--|
| RECYCLED CONTENT |   | PRE: 93% | POST: 0% |  |  |  |  |  |
| <b>~</b>         | MR: PBT Source Reduction (Healthcare)         |          |          |  |  |  |  |  |
| <b>~</b>         | EQ: Daylight                                  |          |          |  |  |  |  |  |
| ~                | EQ: Low-Emitting Materials                    |          |          |  |  |  |  |  |
| <b>~</b>         | MR: Environmental Product Declarations (EPDs) |          |          |  |  |  |  |  |

LEED® is a registered trademark of the U.S. Green Building Council.

**CERTIFICATIONS & PRODUCT DECLARATIONS** 



**EPD AVAILABLE** 

**Certai A**RCHITECTURAL



| AQUAROCK™ |              | FORMAT | DIMENSIONS<br>(IN.) | NRC | CAC | RECYCLED CONTENT | LR   | PIECES/<br>CARTON | SQ. FT./<br>CARTON |    | CARTONS/<br>PALLET |
|-----------|--------------|--------|---------------------|-----|-----|------------------|------|-------------------|--------------------|----|--------------------|
| REVEAL    |              |        |                     |     |     |                  |      |                   |                    |    |                    |
|           | 1182-CRF-1SV | Panels | 24 x 24 x 1/2       | _   | 40  | 93%              | 0.78 | 8                 | 32                 | 65 | 44                 |
|           | 1180-CRF-1SV | Panels | 24 x 48 x 1/2       | _   | 42  | 93%              | 0.78 | 4                 | 32                 | 65 | 44                 |

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

#### **EDGE DETAILS**





Trim 9/16 Grid

Trim 15/16 Grid

### **PHYSICAL DATA**

#### MATERIA

Paperless, moisture-resistant, glass mat faced gypsum board

#### FIRE CLASS

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

#### **ASTM E1264 CLASSIFICATION**

Type XX, Pattern G

#### **VOC EMISSIONS**

Independently certified compliant with California Departmenty of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

#### MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

## MOLD/MILDEW RESISTANCE

Inherently mold-resistant.

## INSTALLATION CONSIDERATION

Consider use with EZ Stab Classic Environmental System if harsh chemicals or moisture will be present.

#### WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

