

Exceptional performance in high-moisture environments and exterior spaces.

**FEATURES AND BENEFITS**

- Paperless, glass mat faced gypsum board that is inherently mold-resistant
- Sag resistant with exceptional indoor/outdoor performance in applications up to 95% relative humidity
- Vinyl facing cleanable with most sanitizing chemicals
- Wash tested to 2,000+ cycles with no sign of wear
- Suited as clean room component to ISO Class 5
- Satisfies USDA/FSIS guidelines for sanitary applications
- Environmental Product Declaration (EPD) available for this product

**ATTRIBUTES**



SAG RESISTANT



LR 0.78



WASHABLE W/  
SANITIZING  
CHEMICALS



EMISSION  
COMPLIANT  
CERTIFIED

**LEED® v4**

RECYCLED CONTENT	93%	
	PRE: 93%	POST: 0%


- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Daylight
- ✓ EQ: Low-Emitting Materials
- ✓ MR: Environmental Product Declarations (EPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

**CERTIFICATIONS & PRODUCT DECLARATIONS**




EPD AVAILABLE


AQUAROCK™	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
<b>REVEAL</b>											
	1182-CRF-1SV	Panels	24 x 24 x 1/2	—	40	93%	0.78	8	32	65	44
	1180-CRF-1SV	Panels	24 x 48 x 1/2	—	42	93%	0.78	4	32	65	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

## EDGE DETAILS



Trim  
9/16 Grid



Trim  
15/16 Grid

## PHYSICAL DATA

### MATERIAL

Paperless, moisture-resistant, glass mat faced gypsum board

### FIRE CLASS

All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

### ASTM E1264 CLASSIFICATION

Type XX, Pattern G

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

### MAINTENANCE

Wash tested to 2,000+ cycles.  
Cleanable with sanitizing chemicals.

### MOLD/MILDEW RESISTANCE

Inherently mold-resistant.

### INSTALLATION CONSIDERATION

Consider use with EZ Stab Classic Environmental System if harsh chemicals or moisture will be present.

### WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](http://certainteed.com/warranty).



## CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com/architectural](http://certainteed.com/architectural)