


MINERAL FIBER FISSURED





Non-directional, sound-absorbing and sound blocking utilitarian panel with exceptional value.

FEATURES AND BENEFITS

- Non-directional fissured pattern
- Three-dimensional face scoring available in 3 geometric designs with Customline options
- Environmental Product Declaration (EPD) available for this product
- Available in (Protectone) version suited for fire assemblies
- Health Product Declaration (HPD) available for this product

ATTRIBUTES







EMISSION COMPLIANT CERTIFIED



RECYCLED CONTENT 33-44%

LEED® v4

RECYCLED CONTENT									
	33%								
CLASS A	PRE: 28%	POST: 5%							
PROTECTONE®	44%								
	PRE: 42%	POST: 2%							

MR: PBT Source Reduction (Healthcare)

✓ EQ: Low-Emitting Materials

✓ EQ: Daylight

MR: Material Ingredients (HPDs)

MR: Sourcing Raw Materials

MR: Environmental Product Declarations (EPDs)

MR: Construction and Demolition Waste Management Planning

LEED* is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS





EPD AVAILABLE


HPD AVAILABLE

BAROQUE™ BAROQUE CUSTOMLINE®

SUSPENSION SYSTEM OPTIONS



CUSTOMLINE SCORING OPTIONS



BAROQUE		FORMAT	DIMENSIONS (MM)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/ CARTON	SQ.M/ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM											
NRC.55	BET-157	Panels	24 x 24 x 5/8	0.55	33	33%	_	16	64	45	20
	PBT-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
	BET-197	Panels	24 x 48 x 5/8	0.55	35	33%	_	8	64	45	20
Z	PBT-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	70	20
	BET-2067	Panels	20 x 60 x 5/8	0.55	35	33%	_	8	67	52	20
REVEAL											
	BET-154	Panels	24 x 24 x 5/8	0.55	33	33%	_	16	64	45	20
NRC.55	PBT-154	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
Z	BET-194	Panels	24 x 48 x 5/8	0.55	35	33%	_	8	64	45	20
NARROW REVEAL											
5	BET-150	Panels	24 x 24 x 5/8	0.55	33	33%	_	16	64	46	20

BAROQUE METRIC	FORMAT	DIMENSIONS (MM)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/ CARTON	SQ. M/ CARTON	LBS./ CARTON	CARTONS/ PALLET
METRIC TRIM										
₩ BET-2067M	Panels	500 x 1500 x 15	0.55	35	33%	_	8	6	52	20
Z Z Z										

BAROQUE CUSTOMLINE		FORMAT	DIMENSIONS (MM)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/ CARTON	SQ. M/ CARTON	LBS./ CARTON	CARTONS/ PALLET	
REVEAL												
	NRC .55	BQCL-224	Panels	24 x 48 x 3/4	0.55	35	33%	-	8	64	55	16
	20	BQCL-448	Panels	24 x 48 x 3/4	0.50	35	33%	-	8	64	55	16
	NRC.5	BQCL-812	Panels	24 x 48 x 3/4	0.50	35	33%	-	8	64	55	16
	Z	PBQCL-224	Panels	24 x 48 x 3/4	0.50	40	44%	Yes*	8	64	75	16

NARROW REVEA	\L										
	BQCLN-224	Panels	24 x 48 x 3/4	0.55	35	33%	-	8	64	55	16
	SE CONTRACTOR DE										
	BQCLN-448	Panels	24 x 48 x 3/4	0.50	35	33%	-	8	64	55	16
	₩ BQCLN-812	Panels	24 x 48 x 3/4	0.50	35	33%	-	8	64	55	16

^{*} Protectone*: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990



PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D - Baroque
Type III, Form 2, Pattern C D K - Customline

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

BAROQUE CUSTOMLINE WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

BAROQUE WARRANTY

1-year Limited Warranty



