



A lightly textured mineral fiber panel with an upscale appearance and effective noise reduction.

FEATURES AND BENEFITS

- Finely textured panel offering an upscale appearance and excellent sound absorption (up to 0.70 NRC)
- Certified VOC compliant
- Cuts cleanly, leading to quicker installation and lower installation costs
- Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product
- USDA Certified Biobased content at 98%
- Some products available in fire-rated (Protectone) versions
- Available in 6 standard colors for item numbers CM-450, CM-454

ATTRIBUTES



**RECYCLED
CONTENT**



**BIOSHIELD®
MOLD/MILDEW
RESISTANT**



**LR
0.82/0.83**



**LOW
VOC
EMISSION
COMPLIANT
CERTIFIED**



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT		
CLASS A	70%	
	PRE: 68%	POST: 2%
PROTECTONE™	44%	
	PRE: 42%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

**CERTIFICATIONS &
PRODUCT DECLARATIONS**



EPD AVAILABLE

HPD AVAILABLE

COLORS



CASHMERE HIGH NRC

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
TRIM													
	NRC .70	CM-457NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	63	16
		CM-497NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
REVEAL													
	NRC .70	CM-454NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16
		CM-494NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
NARROW REVEAL													
	NRC .70	CM-450NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16


CASHMERE

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
TRIM													
	NRC .60	CM-457	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-497	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
REVEAL													
	NRC .60	CM-454	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-494	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	NRC .45	PCM-454	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	70	16
NARROW REVEAL													
	NRC .60	CM-450	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-490	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16


* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column. To specify color other than White, order by item number followed by color code. Example: CM-454 BEB. Color List: Beige Breeze – BEB, Blondewood – BLW, Silver Lining – SIL, Wet Clay – WEC, White Wash – WIW. Only available for CM-454 and CM-450 products.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.


EDGE DETAILS




Trim
9/16 Grid




Trim
15/16 Grid




Reveal
Beveled
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid Bolt Slot



Narrow Reveal
Corner Bevel
9/16 Grid Tier Drop

Color-coordinated suspension systems available

PHYSICAL DATA

MATERIAL
Mineral Fiber

FIRE CLASS
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION
Type III, Form 2, Pattern C E (NRCP only)
Type III, Form 2, Pattern E

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

INSTALLATION CONSIDERATION
Product is lot sensitive. Differing manufacturing dates should not be mixed in a single ceiling or unbroken area.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment.

MOLD/MILDEW RESISTANCE
BioShield® treatment included for added mold and mildew resistance.

WARRANTY
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL PRODUCTS

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
2424 Lakeshore Rd. West, Mississauga, ON L5J 1K4 800-233-8990 certainteed.ca/architectural