



Akusto Wall C Super G fiberglass wall panel features an impact resistant surface.

FEATURES AND BENEFITS

- High impact resistance
- Use as a complement and/or alternative to acoustical ceiling panels for excellent acoustical performance within a space
- Moisture resistant
- Available in 2 standard colors

ATTRIBUTES



LR
0.37 / 0.78



BIOSHIELD®
MOLD/MILDEW
RESISTANT



WASHABLE

LEED® v4

RECYCLED CONTENT	53%	
	PRE: 0%	POST: 53%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE

ECOPHON® AKUSTO™ WALL C SUPER G

COLORS



White




Gray

AKUSTO™ WALL C SUPER G

		COLOR	DIMENSIONS MM(IN.)	NRC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	
WALL PANEL										
	NRC .95	3557 7729	White	2700 x 600 x 40 (= 106 x 24 x 1-1/2)	0.95	0.78	53%	4	21.3 (= 70)	71
		3557 7028	Gray	2700 x 600 x 40 (= 106 x 24 x 1-1/2)	0.95	0.38	53%	4	21.3 (= 70)	71

EDGE DETAILS



Kerfed Edge

PHYSICAL DATA

MATERIAL

Fiberglass

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Washable with mild detergent.

WARRANTY

10-year Ecophon Warranty.

Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL PRODUCTS

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS

2424 Lakeshore Rd. West, Mississauga, ON L5J 1K4 800-233-8990 certainteed.ca/architectural