



Direct-to-deck ceiling solution, ideal for spaces where a traditional suspended ceiling is not possible or desired.

**FEATURES AND BENEFITS**

- Ideal for adding sound absorption (up to 0.80 NRC) to spaces with low or angled ceilings, exposed metal or wooden beams
- 3 direct-to-deck options available: trim, beveled or tongue & groove edges
- Direct-to-deck attachment with adhesive (Focus B, F, SQ)
- Direct-to-deck attachment by concrete screws or indirect attachment to wood furring (Focus F)
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, reinforced edges that resist damage from handling
- Available in 22 standard colors (Focus B & SQ Only)

**ATTRIBUTES**



**RECYCLED  
CONTENT**



**BIOSHIELD®  
MOLD/MILDEW  
RESISTANT**



**LR 0.85  
(WHITE ONLY)**



**WASHABLE**



**SAG  
RESISTANT**

**LEED® v4**

<b>RECYCLED CONTENT</b>	<b>51%</b>	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

**CERTIFICATIONS & PRODUCT DECLARATIONS**



EPD AVAILABLE



HPD AVAILABLE

**COLORS**



**FOCUS B**

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
<b>BEVELED</b>											
	<b>NRC .75</b>	3542 2900	Panels	600 x 600 x 20 (≈ 24 x 24 x 3/4)	0.75	—	51%	20	7.2 (≈ 77.5)	49	—

**FOCUS F**

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
<b>TONGUE &amp; GROOVE</b>											
	<b>NRC .80</b>	3542 2800	Panels	600 x 600 x 20 (≈ 24 x 24 x 3/4)	0.80	—	51%	20	7.2 (≈ 77.5)	47	—
		3542 2801	Panels	600 x 1200 x 20 (≈ 24 x 48 x 3/4)	0.80	—	51%	10	7.2 (≈ 77.5)	47	—




**FOCUS SQ**

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
<b>SQUARE</b>											
	<b>NRC .75</b>	3540 3645	Panels	600 x 600 x 20 (≈ 24 x 24 x 3/4)	0.75	—	51%	20	7.2 (≈ 77.5)	41	—
		3540 3646	Panels	600 x 1200 x 20 (≈ 24 x 48 x 3/4)	0.75	—	51%	12	8.6 (≈ 93)	40	—

All Focus B and SQ panels listed above are white. To order colors please contact your local Sales Representative.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

## ACCESSORIES

FOCUS B, F, & SQ ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE	
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
FOCUS F ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE	
	2630 1219	Connect Spine	50	Installed on 24 inch centers
	2630 0149	Connect Direct Fixing Plate (Focus F)	100	Installed on 24 inch centers

\*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

## EDGE DETAILS



## PHYSICAL DATA

**MATERIAL**  
Fiberglass

**ASTM E1264 CLASSIFICATION**  
Type XII, Form 2, Pattern G

**FIRE CLASS (ASTM E1264)**  
All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

**WARRANTY**  
10-year Ecophon® Warranty.  
Full warranty information can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



### CertainTeed ARCHITECTURAL PRODUCTS

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS  
2424 Lakeshore Rd. West, Mississauga, ON L5J 1K4 800-233-8990 [certainteed.ca/architectural](https://www.certainteed.ca/architectural)