



Semi-concealed grid provides unique aesthetics coupled with superior sound absorption in a wide selection of sizes and colors.

FEATURES AND BENEFITS

- Semi-concealed, easy downward access
- Narrow gap between panels (5/16")
- Terminus Fin Semi-Concealed Accessory available for finishing of cloud perimeter
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, damage-resistant concealed edges
- Available in 22 standard colors

ATTRIBUTES



**RECYCLED
CONTENT**



**BIOSHIELD®
MOLD/MILDEW
RESISTANT**



**LR 0.85
(WHITE)**



WASHABLE



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS




EPD AVAILABLE



HPD AVAILABLE

COLORS



FOCUS DG		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
SEMI-CONCEALED											
	NRC-.90	3542 1560	Panels	24 x 24 x 3/4	0.90	—	51%	20	80	44	n/a
		3542 1561	Panels	24 x 48 x 3/4	0.90	—	51%	10	80	44	n/a
		3542 4239	Panels	30 x 30 x 3/4	0.90	—	51%	14	87.5	43	n/a
		3542 1565	Panels	48 x 48 x 1	0.90	—	51%	6	96	64	n/a
		3542 1562	Planks	24 x 60 x 3/4	0.90	—	51%	6	60	33	n/a
		3542 1563	Planks	24 x 72 x 3/4	0.90	—	51%	6	72	36	n/a
		3542 1564	Planks	24 x 96 x 3/4	0.90	—	51%	6	96	53	n/a

All Focus panels listed above are white. To order colors please contact your local Sales Representative.








CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES


FOCUS DG ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE	
	2630 0547	Connect Dg 20 Support Clip	50	For support of any cut supporting edge on 3/4" Dg or Ds (typically 1 pc. every 12 - 18 inches)
	2630 0547	Connect Dg 25 Support Clip	50	For support of any cut supporting edge on 1" Dg 4x4 panels only (typically 1 pc. every 12 - 18 inches)
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
	2630 0991	Connect Dg Cutting Tool	1	For rabbeting field-cut edges
	2630 0546	Connect Edge Clip	12	Required for non-supporting edges on all 1" Dg 4x4 panels only (2/panel)
	2630 0824	Connect Wall Bracket T-Profile	25	For main runner attachment to wall (typically 2/run of main runner)
	2631 1080	Connect Perimeter Tile Clip	100	For attachment and securing panels at the perimeter
	STBAR-2	CTC 2' Stabilizer Bar	40	For all 2x5, 2x6, 2x8 applications; typically 1 pc./panel for 2x5, 2x6, 2 pc. /panel for 2x8

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

ACCESSORIES

FOCUS WING & WING ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE
	3549 1060 Focus Wing DS Straight Kit	3	Perimeter treatment for clouds or peninsulas; straight 48 x 8 x 2 full-concealed panel
	3549 1061 Focus Wing DS External Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for external corners containing 56 x 8 x 2 panel with mitered corner
	3549 1062 Focus Wing DS Internal Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for internal corners containing 56 x 8 x 2 panel with mitered corner
	2630 0650 Connect Wing Distance	2	For connection of Wing to Wing (typically 1 pc./Wing intersection)
	2630 0666 Connect Hook	1	For connection between Wing Corner pieces (typically 1 pc./corner)
	2630 0187 Connect Wall Spring Spacer	24	For use when trim cutting panels at the perimeter
	2631 1040 Connect L-coupling	50	For use every time a field grid member intersects with the perimeter main runners

EDGE DETAILS



PHYSICAL DATA

MATERIAL
Fiberglass

ASTM E1264 CLASSIFICATION
Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon® Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural