



Fully concealed suspension system coupled with superior sound absorption in a wide selection of sizes and colors.

FEATURES AND BENEFITS

- Fully concealed, easy downward access
- Monolithic surface simulates drywall finished appearance
- Terminus Fin Semi-Concealed Accessory available for finishing of cloud perimeter
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, damage-resistant concealed edges
- Available in 22 standard colors

ATTRIBUTES



**RECYCLED
CONTENT**



**BIOSHIELD®
MOLD/MILDEW
RESISTANT**



**LR 0.85
(WHITE)**



WASHABLE



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE

COLORS
















FOCUS DS

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
FULLY-CONCEALED											
	NRC .85	3542 1511	Panels	24 x 24 x 3/4	0.85	25	51%	20	80	44	n/a
		3542 1512	Panels	24 x 48 x 3/4	0.85	25	51%	10	80	44	n/a
		3542 1516	Panels	48 x 48 x 3/4	0.85	25	51%	6	96	50	n/a
		3542 1513	Planks	24 x 60 x 3/4	0.85	25	51%	6	60	33	n/a
		3542 1514	Planks	24 x 72 x 3/4	0.85	25	51%	6	72	45	n/a
		3542 1515	Planks	24 x 96 x 3/4	0.85	25	51%	6	96	50	n/a

All Focus Ds products listed are white. To order colors please contact your local Sales Representative.








CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES


FOCUS DS ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE	
	2630 0547	Connect Dg 20 Support Clip	50	For support of any cut supporting edge on 3/4" Dg or Ds (typically 1 pc. every 12 - 18 inches)
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
	2630 0991	Connect Dg Cutting Tool	1	For rabbeting field-cut edges
	STBAR-2	CTC 2' Stabilizer Bar	40	For all 2x5, 2x6, 2x8 applications; typically 1 pc./panel for 2x5, 2x6, 2 pc. /panel for 2x8
	STBAR-4	CTC 4' Stabilizer Bar	40	For all 2x6, 2x8 applications; typically 1 pc./panel for 2x6, 2 pc. /panel for 2x8
	EZCS12-12-20	15/16" Classic Stab HD Main Runner		For use only with Connect Space Bar 0577
	2630 0577	Ecophon® Connect Space Bar	10	For use only with CTC HD CS12-12-20, spaced every 48" on center, max 24" away from the wall
	2630 0524	Connect Wall Bracket T-Profile	50	For main runner attachment to wall (typically 2/run of main runner)
	2630 0525	Connect Space Bar Wall Bracket	10	For attachment of space bar to wall (typically 2/run of space bar)
	2630 0853	Connect Space Bar Winch	100	For attachment of space bar to main runner (one pc. for each intersection)
	2630 0381	Connect Edge Stiffner	12	Required for Focus™ Ds 4x4 systems (2 pc./panel)
	2631 1080	Connect Perimeter Tile Clip	100	For attachment and securing panels at the perimeter
	2630 0196	Connect Hold Down Clip Ds	100	For use as a hold down clip with Focus Dg and Focus Ds (typically 1 pc./sf for 2x2 and 0.65 pc./sf for 2x4)

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

ACCESSORIES

FOCUS WING & WING ACCESSORIES	PRODUCT NAME	PIECES/CARTON	USE
	3549 1060 Focus Wing DS Straight Kit	3	Perimeter treatment for clouds or peninsulas; straight 48 x 8 x 2 full-concealed panel
	3549 1061 Focus Wing DS External Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for external corners containing 56 x 8 x 2 panel with mitered corner
	3549 1062 Focus Wing DS Internal Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for internal corners containing 56 x 8 x 2 panel with mitered corner
	2630 0650 Connect Wing Distance	2	For connection of Wing to Wing (typically 1 pc./Wing intersection)
	2630 0666 Connect Hook	1	For connection between Wing Corner pieces (typically 1 pc./corner)
	2630 0187 Connect Wall Spring Spacer	24	For use when trim cutting panels at the perimeter
	2631 1040 Connect L-coupling	50	For use every time a field grid member intersects with the perimeter main runners

EDGE DETAILS



PHYSICAL DATA

MATERIAL
Fiberglass

ASTM E1264 CLASSIFICATION
Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon® Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural