



Sound absorbing wall panel suitable for even the most demanding conditions, from intensive care units and operation rooms, to patient rooms and airtight laboratories.

**FEATURES AND BENEFITS**

- Designed to facilitate daily cleaning with strong sanitizers and disinfectant chemicals
- Virtually zero particle emission, ensuring high indoor air quality. Suitable as a clean room component (ISO Class 3)
- Fully encapsulated in a smooth, high-performance film that is impervious to particles and water to repel dirt
- Quick and easy installation; stainless steel wall brackets screw into place, and wall panel simply slides into the brackets
- Easy removability allows 360-degree cleaning of the panels and the wall behind them
- Satisfies 2018 FGI Guidelines for use in restricted areas (such as operating rooms)
- Excellent sound absorption with a 0.90 NRC
- VOC Compliant to CDPH v1.2, 2017

**ATTRIBUTES**



**BIOSHIELD®  
MOLD/MILDEW  
RESISTANT**



**EMISSION  
COMPLIANT  
CERTIFIED**



**RECYCLED  
CONTENT**


**LEED® v4**

<b>RECYCLED CONTENT</b>	<b>38%</b>	
	PRE: 0%	POST: 38%


- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ EQ: Low-emitting Materials

LEED® is a registered trademark of the U.S. Green Building Council.


# ECOPHON® HYGIENE ADVANCE™ WALL

HYGIENE ADVANCE™ WALL	COLOR	DIMENSIONS MM(IN.)	NRC	SABINS/ UNIT	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	
WALL PANEL										
	3513 8030	White	592 x 1192 (= 23-5/16 x 46-15/16)	0.90	6.8	0.73	38% post	6	46	39

## ACCESSORIES

HYGIENE ADVANCE WALL ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE	
	2630 0716	Connect Wall Fixing (stainless steel)	12	2 per panel for vertical installation, 4 per panel for horizontal installation

## EDGE DETAILS



## PHYSICAL DATA

### MATERIAL

Fiberglass  
Fully-encapsulated in a smooth, impervious high-performance film

### FIRE CLASS (ASTM E1264)

#### CLASS A FOR US AND CANADA

Tested according to ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

### MOLD/MILDEW RESISTANCE

Fiberglass substrate is fully-encapsulated by water-impervious film.

### MAINTENANCE

Refer to online maintenance instructions.

### WARRANTY

10-year Ecophon Warranty.  
Full warranty information can be found at [certainteed.com/warranty](http://certainteed.com/warranty).

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.



## CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS  
20 Moores Road, Malvern, PA 19355 800-366-4327 [certainteed.com/architectural](http://certainteed.com/architectural)