



Specially designed for when low particulate emission and maximum cleanliness are essential.

FEATURES AND BENEFITS

- Encapsulated gypsum core-board. Vinyl face/back with sealed edges.
- Wash tested to 2,000+ cycles with no sign of wear
- Surface suitable for cleaning with common sanitizing chemicals
- Exceeds FGI guidelines for cleanability in healthcare spaces
- Satisfies USDA/FSIS guidelines for sanitary applications
- Suited as clean room component to ISO Class 5
- Environmental Product Declaration (EPD) available for this product

ATTRIBUTES



LR 0.78



SAG
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE



WASHABLE W/
SANITIZING
CHEMICALS

LEED® v4

RECYCLED CONTENT	99%	
	PRE: 94%	POST: 5%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Low-Emitting Materials
- ✓ Q: Daylight
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Environmental Product Declarations (EPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



ENVIROGARD™	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM										
	1192-CRF-1	Panels	24 x 24 x 1/2	—	34	99%	8	32	47	44
	1190-CRF-1	Panels	24 x 48 x 1/2	—	36	99%	4	32	47	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES

ENVIROGARD ACCESSORIES	PRODUCT NAME	PIECES/CARTON	USE
	1190-SEL-1	1	For re-sealing cut edges; 1 quart container

EDGE DETAILS



PHYSICAL DATA

MATERIAL
Gypsum

ASTM E1264 CLASSIFICATION
Type XX, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE
Wash tested to 2,000+ cycles.
Cleanable with sanitizing chemicals.

INSTALLATION CONSIDERATION
Should be installed with an environmental suspension system such as EZ Stab Classic Environmental.

WARRANTY
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural