SUBMITTAL SHEET HIGH PROFILE SERIES™ VERTICALLY CURVED

Project Name_____ Specification Section_____ Ceiling Type_____

SUBSTRATE	Extruded Aluminum
PROFILE	 ✓ Beam (1-1/2" x 6-3/8") * Length - minimum 4'-0", maximum 20'-0"
BEAM SPACING	□ 6" □ 8" □ 12" □ Other
VERTICAL CURVATURE	Radius: (Minimum 48", except where otherwise specified) * For multiple radii, or two radii on the same beam, contact manufacturer.
COLOR/FINISH	Beam Finish Cotton White - #0280 Natural - #7163 Other
	Hanger Bracket Finish Black White Painted to match plenum
END CAPS	□ Yes □ No
EXPOSURE	☑ Interior Only

Shop Drawings required on all High Profile projects.





PHYSICAL DATA

Substrate: Aluminum
Warranty: 1 year Limited Warranty
Seismic rating: Zones A,B,C,D,E,F
Fire rating: Class A Fire Rated per ASTM E84

Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
Class A Fire Rated per CAN/ULC-S102

Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 2.0 - 4.0 lbs./sq.ft.

Wind load: N/A

Recycled content: Minimum of 50%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81