



A perfect combination of strength and flexibility, innovative Techstyle delivers larger panels that are lighter, easier to install, and far less prone to damage. Smooth surfaces produce higher color coverage for brighter whites, more vivid colors, and more realistic wood grains and patterns.

FEATURES AND BENEFITS

- Creates a clean, monolithic aesthetic
- Exceptional sound absorption
- Wide variety of trim profiles allows direct wall attachment, floating clouds, and fixture integration
- Standard, large format, and custom-sized swing-down panels mask the appearance of suspension systems with semi-concealed edges and nominal 1/4" reveals
- Two panel types: Lay-in and Swing-down for easy plenum access
- Proprietary formaldehyde-free fiberglass composite construction
- Sag resistant for exceptional indoor performance

ATTRIBUTES



**SAG
RESISTANT**



**MOLD/MILDEW
RESISTANT
INHERENT**



**LR: 0.88
(ASTM E1264)**



**EMISSION
COMPLIANT
CERTIFIED**



NRC 0.85

LEED® v4

RECYCLED CONTENT

up to 10%

- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS



HPD AVAILABLE*



**GREENGUARD
GOLD
CERTIFIED**

*Felt currently not available with HPD


COLORS AND FINISHES

A wide choice of colors and finishes as well as custom color matching are available upon request. See website for the most up to date information and to order samples.

NOTE: Colors are for illustration purposes only.


TECHSTYLE COLOR

Smooth polyester non-woven fabric




TECHSTYLE WOOD

Smooth polyester non-woven fabric




TECHSTYLE FELT

smooth polyester non-woven fabric



TECHSTYLE WHITE

Ultra-smooth fiberglass matte surface




TECHSTYLE CUSTOM


smooth polyester non-woven fabric

- Custom color and woodgrain matches
- Stripes, textures and patterns
- Letters, words and logos
- For custom options, contact your local Sales Rep. at certainteed.com/ceilings or call 800-807-7325.



STANDARD PRODUCT OPTIONS


TECHSTYLE	Format	Dimensions W x L (in.)	Lbs./ Sq. Ft.
SWING DOWN PANELS			
	Panels	24 x 6	0.30
	Panels	24 x 24	0.30
	Panels	24 x 48	0.30
	Large Format Panels	24 x 60*	0.30
	Large Format Panels	24 x 72*	0.30
	Large Format Panels	24 x 96*	0.30
	Panels	30 x 6	0.30
	Panels	30 x 24	0.30
	Panels	30 x 30	0.30
	Panels	30 x 48	0.30
	Large Format Panels	30 x 60*	0.30
	Large Format Panels	30 x 72*	0.30
	Large Format Panels	30 x 96*	0.30
	Panels	48 x 6	0.30
	Panels	48 x 24	0.30
	Panels	48 x 48*	0.30
Large Format Panels	48 x 60*	0.30	
Large Format Panels	48 x 72*	0.30	

TECHSTYLE	Format	Dimensions W x L (in.)	Lbs./ Sq. Ft.
LAY-IN PANELS			
	Panels	24 x 24	0.24
	Panels	24 x 48	0.24
	Large Format Panels	24 x 60	0.24
	Large Format Panels	24 x 72	0.24
	Large Format Panels	24 x 96	0.24
	Large Format Panels	24 x 144	0.24
	Panels	30 x 24	0.24
	Panels	30 x 30	0.24
	Panels	30 x 48	0.24
	Large Format Panels	30 x 60	0.24
	Large Format Panels	30 x 72	0.24
	Large Format Panels	30 x 96	0.24
	Large Format Panels	30 x 144	0.24
	Panels	48 x 24	0.24
	Panels	48 x 48	0.24
	Large Format Panels	48 x 60	0.24
Large Format Panels	48 x 72	0.24	
Large Format Panels	48 x 96	0.24	


*Requires use of Mid-Span Support Clips

CAN'T FIND A SIZE? Contact your local Sales Representative at CertainTeed.com/ceilings or call 800-807-7325


SUSPENSION SYSTEM OPTIONS



Swing Down
15/16 T-Grid
Compatible with all 15/16"
EZ Stab Suspension Systems



Lay-In
15/16 T-Grid



Techstyle Grid System (Echelon)
compatible with both swing
down and lay-in panels



Comprised of fiberglass, each Techstyle panel features a unique channeled honeycomb structure making the panels lightweight, dimensionally stable, easy to handle and simple to install.

For additional information on the Techstyle Grid System, please visit the website at CertainTeed.com/Techstyle

ACCESSORIES

STANDARD TRIM OPTIONS – All trims extruded aluminum

DIRECT MOUNT		WALL TRIMS		FLOATING TRIMS						FIXTURE TRIMS	
DM3 NARROW	DM2 WALL	WT1	WT2	FT2	FT3	FT4	FT6	FT8	FT2A	FIXTURE TRIM FLANGE	FIXTURE TRIM REVEAL
(wall application only)											

STANDARD ACCESSORIES	Item Number	Product Name	Pieces/carton	Use
	409034	TC2 Clip	1	Used to attach floating trim to grid members
	409045	Grid Squaring Bracket	80	Recommended accessory to assist with squaring grid. When necessary use two per panel at opposite corners
	409134	Connector Clip - Trim to Trim	1	Used to connect straight pieces of perimeter trim together
	409132	Inside Corner Connector	1	Used to connect perimeter trim pieces at inside corners
	409133	Outside Corner Connector	1	Used to connect perimeter trim pieces at outside corners
	409144	Panel Spring	25	Used to create a consistent reveal when perimeter panels are cut too short
	409143	Panel Screw	25	Used to create a consistent reveal when perimeter panels are cut too short
	409037	Mid-span Support Clip	21	Used to prevent deflection. Required on specific panel sizes as defined on page 3
	409137	Foam Spacer	50	Used within perimeter trim to keep consistent reveal between panels
	408879	DMI Rail Clip	25	Used to attach DMI rail to the wall/deck
	409002	DMI Rail Spacer	100	Used to keep a consistent 1/4" reveal between panels that are attached to the DMI rail

CUSTOM CURVED ACCESSORIES – In-house curving capabilities. Contact factory for more information at 800-807-7325




Typical Outside Radius



Typical Inside Radius



Techstyle Wood | Muskego Lakes Middle School



Techstyle White | Emerald Hills | Photo: © Shai Gil Photography courtesy of Sound Solutions

PHYSICAL DATA

MATERIAL

Surface Finish: Polyester Non-Woven Fabric Surface (Color, Wood, Felt, Custom)

Surface Finish: Fiberglass Matte Surface (White).

FIRE CLASS

Class A per ASTM E1264 & CAN/ULC S102 (White, Color, Wood, Custom, Felt)

SYSTEM WEIGHT

<1 lb / SF

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. GreenGuard Gold Certified

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

FINGER PRINTS & INSTALLATION MARKS:
During Installation: Use a cut out piece of tile, face to face, rubbing gently until dirt disappears. If a mark is particularly deep or dark, a lightly moistened microfiber sponge should be used.
During Maintenance: A lightly moistened microfiber sponge should be used.

VENT DIRT: The dirty area may be lightly vacuumed. If additional cleaning is needed, microfiber sponge should be used. Wipe gently. For best results, replace the vent filters regularly.

WARRANTY

10 Year-Limited Warranty. Full warranty information can be found at certainteed.com/techstyle.



Techstyle Color | Logan airport



Techstyle Custom | National Interstate Insurance



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-807-7325 certainteed.com/architectural